

Product Specifications	Standard	Rolls & Tiles	Raised Access Floor Tiles (Square and Plank)
<b>Composition</b>	-	87%vinyl + 13% polyester + backing100% vinyl	87%vinyl + % polyester + backing100% vinyl
<b>Weight (g/m²) (oz/sq ft)</b>	ISO 8543:1998	3500 g/m² (11.5 oz/sq ft) +13% / -10%	4275 g/m² (14.0 oz/sq ft) +13% / -10%
<b>Thickness (mm.) (in)</b>	ISO 1765:1986	2.60 mm (0.10 in)	3.30 mm (0.13 in)
<b>Light Fastness (Grey scale: 1-5)</b>	EN ISO 4892:2006 (exterior)	>4/5	>4/5
<b>Light Fastness (Blue scale: 1-8)</b>	EN ISO 105B02:2001 (interior)	>7/8	>7/8
<b>Dimensional Stability %</b>	EN ISO 23999:2012	≤0.25%	≤0.25%
<b>Residual Indentation</b>	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
<b>Castor Chair Test</b>	EN 985:2002	Intensive use	Intensive use
<b>Sound Insulation</b>	EN ISO 10140-3:2011	14 dB	15 dB
<b>Thermal Resistance</b>	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
<b>Static Electricity</b>	EN 1815:1997	< 2 kV	< 2 kV
<b>Slip Resistance</b>	EN 13893:2003	>0.4	>0.4
<b>Slip Resistance</b>	DIN 51130:2014	R9	R9
<b>Slip Resistance</b>	ASTM C1028-96 Static Coefficient	Wet: 0.62; Dry: 0.70	Wet: 0.62; Dry: 0.70
<b>Fire Classification</b>	EN 13501-1:2007	Bfl-S1	Bfl-S1
<b>Fire Classification</b>	ASTM E648 (NFPA 253)	Class 1	Class 1
<b>Antibacterial activity</b>	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
<b>Roll Width</b>	-	200 cm 78.740 in	
<b>Roll Length</b>	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
<b>CE Certificate</b>	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
<b>Use Classification</b>	EN 1307:2014	Heavy Commercial	
<b>Tile Dimensions</b>			

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

Product Specifications	Standard	Rolls & Tiles (Rolls only for corridors)	Raised Access Floor Tiles (Square and Plank)
<b>Composition</b>	-	75%vinyl + 25% polyester + backing 100% vinyl	75% vinyl + 25% polyester + backing 100% vinyl
<b>Weight (g/m²) (oz/sq ft)</b>	ISO 8543:1998	3100 g/m² (10.2 oz/sq ft) +13% / -10%	4300 g/m² (14.1 oz/sq ft) +13% / -10%
<b>Thickness (mm.) (in)</b>	ISO 1765:1986	2.30 mm (0.09 in)	3.00 mm (0.12 in)
<b>Light Fastness (Grey scale: 1-5)</b>	EN ISO 4892:2006 (exterior)	>4/5	>4/5
<b>Light Fastness (Blue scale: 1-8)</b>	EN ISO 105B02:2001 (interior)	>7/8	>7/8
<b>Dimensional Stability %</b>	EN ISO 23999:2012	≤0.25%	≤0.25%
<b>Residual Indentation</b>	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
<b>Castor Chair Test</b>	EN 985:2002	Intensive use	Intensive use
<b>Sound Insulation</b>	EN ISO 10140-3:2011	12 dB	13 dB
<b>Thermal Resistance</b>	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
<b>Static Electricity</b>	EN 1815:1997	< 2 kV	< 2 kV
<b>Slip Resistance</b>	EN 13893:2003	>0.4	>0.4
<b>Slip Resistance</b>	DIN 51130:2014	R10	R10
<b>Slip Resistance</b>	ASTM C1028-96 Static Coefficient	Wet: 0.79; Dry: 0.86	Wet: 0.79; Dry: 0.86
<b>Fire Classification</b>	EN 13501-1:2007	Bfl-S1	Bfl-S1
<b>Fire Classification</b>	ASTM E648 (NFPA 253)	Class 1	Class 1
<b>Antibacterial activity</b>	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
<b>Roll Width</b>	-	200 cm 78.740 in	
<b>Roll Length</b>	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
<b>CE Certificate</b>	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
<b>Use Classification</b>	EN 1307:2014	Heavy Commercial	
<b>Tile Dimensions</b>	<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p>Square</p> <p>50cm/100cm</p> </div> <div style="text-align: center;"> <p>Plank</p> <p>25cm 76cm</p> </div> <div style="text-align: center;"> <p>Brick</p> <p>50cm 100cm</p> </div> <div style="text-align: center;"> <p>Diamond</p> <p>50cm 50cm</p> </div> <div style="text-align: center;"> <p>Hexagon</p> <p>61.4cm 30.7cm</p> </div> <div style="text-align: center;"> <p>E. Triangle</p> <p>50cm 50cm</p> </div> <div style="text-align: center;"> <p>I. Triangle</p> <p>50cm 70.7cm</p> </div> <div style="text-align: center;"> <p>Trap</p> <p>61.4cm 27cm</p> </div> <div style="text-align: center;"> <p>Arcade</p> <p>75cm 50cm</p> </div> </div>		

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

**vertisol**  
contemporary weavers

C. 17Km.18, 920-08403 Granollers (Barcelona), Spain  
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19

fitnice® is a registered trademark of Vertisol Internacional SRL.

fitnice.com  
info@fitnice.com

fitniceflooring



ISO 9001:2015 and  
ISO 14001:2015  
certified company



Product Specifications	Standard	Rolls & Tiles	Raised Access Floor Tiles (Square and Plank)
<b>Composition</b>	-	91% vinyl + 9% polyester + backing 100% vinyl	91% vinyl + 9% polyester + backing 100% vinyl
<b>Weight (g/m<sup>2</sup>) (oz/sq ft)</b>	ISO 8543:1998	3500 g/m <sup>2</sup> (11.5 oz/sq ft) +13% / -10%	4275 g/m <sup>2</sup> (14.0 oz/sq ft) +13% / -10%
<b>Thickness (mm) (in)</b>	ISO 1765:1986	2.70 mm (0.11 in)	3.35 mm (0.13 in)
<b>Light Fastness (Grey scale: 1-5)</b>	EN ISO 4892:2006 (exterior)	>4/5	>4/5
<b>Light Fastness (Blue scale: 1-8)</b>	EN ISO 105B02:2001 (interior)	>7/8	>7/8
<b>Dimensional Stability %</b>	EN ISO 23999:2012	≤0.25%	≤0.25%
<b>Residual Indentation</b>	EN ISO 24343-1:2012	<0.30 mm (<0.011 in)	<0.30 mm (<0.011 in)
<b>Castor Chair Test</b>	EN 985:2002	Intensive use	Intensive use
<b>Sound Insulation</b>	EN ISO 10140-3:2011	14 dB	15 dB
<b>Thermal Resistance</b>	EN 12667:2001	< 0.15m <sup>2</sup> K/W	< 0.15m <sup>2</sup> K/W
<b>Static Electricity</b>	EN 1815:1997	< 2 kV	< 2 kV
<b>Slip Resistance</b>	EN 13893:2003	>0.4	>0.4
<b>Slip Resistance</b>	DIN 51130:2014	R9	R9
<b>Slip Resistance</b>	ASTM C1028-96 Static Coefficient	Wet: 0.59; Dry: 0.72	Wet: 0.59; Dry: 0.72
<b>Fire Classification</b>	EN 13501-1:2007	Bfl-S1	Bfl-S1
<b>Fire Classification</b>	ASTM E648 (NFPA 253)	Class 1	Class 1
<b>Antibacterial activity</b>	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
<b>Roll Width</b>	-	200 cm 78.740 in	
<b>Roll Length</b>	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
<b>CE Certificate</b>	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
<b>Use Classification</b>	EN 1307:2014	Heavy Commercial	
<b>Tile Dimensions</b>			

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

**vertisol**  
contemporary weavers

C. 17Km. 18, 920 · 08403 Granollers (Barcelona), Spain  
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19

fitnice® is a registered trademark of Vertisol Internacional SRL.



fitnice.com  
info@fitnice.com

fitniceflooring



















ISO 9001:2015 and  
ISO 14001:2015  
certified company



Product Specifications	Standard	Rolls & Tiles	Raised Access Floor Tiles (Square and Plank)
<b>Composition</b>	-	75% vinyl + 25% polyester + backing 100% vinyl	75% vinyl + 25% polyester + backing 100% vinyl
<b>Weight (g/m<sup>2</sup>) (oz/sq ft)</b>	ISO 8543:1998	2900 g/m <sup>2</sup> (9.5 oz/sq ft) +13% / -10%	4500 g/m <sup>2</sup> (14.75 oz/sq ft) +13% / -10%
<b>Thickness (mm.) (in)</b>	ISO 1765:1986	2.25 mm (0.09 in)	2.90 mm (0.11 in)
<b>Light Fastness (Grey scale: 1-5)</b>	EN ISO 4892:2006 (exterior)	>4/5	>4/5
<b>Light Fastness (Blue scale: 1-8)</b>	EN ISO 105B02:2001 (interior)	>7/8	>7/8
<b>Dimensional Stability %</b>	EN ISO 23999:2012	≤0.25%	≤0.25%
<b>Residual Indentation</b>	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
<b>Castor Chair Test</b>	EN 985:2002	Intensive use	Intensive use
<b>Sound Insulation</b>	EN ISO 10140-3:2011	13 dB	14 dB
<b>Thermal Resistance</b>	EN 12667:2001	< 0.15 m <sup>2</sup> K/W	< 0.15 m <sup>2</sup> K/W
<b>Static Electricity</b>	EN 1815:1997	< 2 kV	< 2 kV
<b>Slip Resistance</b>	EN 13893:2003	>0.4	>0.4
<b>Slip Resistance</b>	DIN 51130:2014	R10	R10
<b>Slip Resistance</b>	ASTM C1028-96 Static Coefficient	Wet: 0.65; Dry: 0.75	Wet: 0.65; Dry: 0.75
<b>Fire Classification</b>	EN 13501-1:2007	Bfl-S1	Bfl-S1
<b>Fire Classification</b>	ASTM E648 (NFPA 253)	Class 1	Class 1
<b>Antibacterial activity</b>	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
<b>Roll Width</b>	-	200 cm (78.740 in)	
<b>Roll Length</b>	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
<b>CE Certificate</b>	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
<b>Use Classification</b>	EN 1307:2014	Heavy Commercial 	
<b>Tile Dimensions</b>			

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

Product Specifications	Standard	Rolls & Tiles
 <b>Composition</b>	-	75%vinyl + 25% polyester + backing 100% PVC
 <b>Weight (g/m²)</b>	EN ISO 23997:2012	3300 g/m² +13% / -10%
 <b>Thickness (mm)</b>	EN24346:2012	2.35 mm (+0.15mm/-0.1mm)
 <b>Light Fastness (Grey scale:1-5)</b>	EN ISO 4892:2006 (exterior)	≥4/5
 <b>Light Fastness (Blue scale:1-8)</b>	EN ISO 105 B02:2001 (interior)	≥7
 <b>Dimensional Stability %</b>	EN ISO 23999:2012	Approved
 <b>Residual Indentation</b>	EN ISO 24343-1:2012	<0.1mm
 <b>Sound Insulation</b>	EN ISO 10140-3:2011	13 dB
 <b>Slip Resistance</b>	EN 13893:2003	>0.35
<b>Slip Resistance</b>	DIN 51130:2014	R10
 <b>Fire Classification</b>	IMO MSC.307 (88)	Pass
<b>Corrosion in ambience of saline neutral fog</b>		No changes after 240h exposure
<b>Use Classification</b>	ISO10874:2012	Heavy Commercial 
 <b>Tile Dimensions</b>	All colours are available in:  <div style="display: flex; justify-content: space-around; align-items: flex-end;"> <div style="text-align: center;"> <p>Roll</p>  <p>2mt</p> </div> <div style="text-align: center;"> <p>Square</p>  <p>50cm/100cm</p> </div> <div style="text-align: center;"> <p>Plank</p>  <p>25cm 75cm</p> </div> <div style="text-align: center;"> <p>Diamond</p>  <p>50cm 50cm</p> </div> </div> <p>Recommended for tiles only. If in rolls, seams may be visible.</p>	

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

**vertisol**  
contemporary weavers

C. 17Km. 18, 920-08403 Granollers (Barcelona), Spain  
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19

fitnice® is a registered trademark of Vertisol Internacional SRL.

fitnice.com  
info@fitnice.com

  fitniceflooring